Wenzhou Safewire Electric CO.,Ltd.

SPECIFICATION SHEET

PRODUCT NAME: 10A A/V socket







KC1-072

KC1-075

KC1-076

ADD: 152 xinguang industrial zone, yueqing city, zhejiang province

(TEL):0086-18612380398

(E-mail): info@safewirele.com (WEB): http://www.safewirele.com

Product Details

Serial No.	Parameter	Description
1	Place of Origin	Zhejiang, China
2	Brand Name	Safewire or OEM Brand
3	Panel Material	PC
4	Back	PC or PC+IRON



Wenzhou Safewire Electric Co.,Ltd.

No.152 Xingguang Road, Xingguang industry zone, Liushi town, Yueqing, Wenzhou, China ,325604

5	Inside	phosphor cooper
6	Touch point	silver alloy
7	Rated Current	10A
8	Rated voltage	220~250V
9	Mechanical Life	40000times
10	Color	White
11	Certificate	CE/IEC/SASO/COC
12	Style	Wall Socket
13	Warranty	10 years

Product Show:



A/V socket with VGA socket

KC1-072

10A/250V~ 10pcs/box 100pcs/ctn 49.5x31.5x20cm³



A/V socket and HD socket, Audio play 10A/250V~ 10pcs/box 100pcs/ctn 49.5x31.5x20cm³ KC1-075

KC1-076



A/V socket and VGA, Audio play

10A/250V~ 8pcs/box 80pcs/ctn 49.5x31.5x20cm³

Features:

- 1.86*86 size, the most popular size in the market.
- 2.High-quality PC material.Flame retardant,high strength,high temperature resistance,not easy to fade.
- 3. Silver contacts, conductive, arc resistant, Tin phosphorus bronze current carrying gold parts, excellent electrical conductivity.
- 4. Precise structure, switch facepllate all in one, easy to assemble and dismantle.
- 5. This one gang one way dimmer have a switch to control dimmer on-off.

Products inside: Brass and Copper, Silvery touching point



Application:

Residential / General-Purpose, House, Indoor, School, Office,

Building, Hotel, Residential, villa, home



Wenzhou Safewire Electric Co.,Ltd.

No.152 Xingguang Road, Xingguang industry zone, Liushi town, Yueqing, Wenzhou, China ,325604

Attentions:

- 1. When installing and wiring, Product should avoid direct contact with corrosive liquid, gas (strong acid, strong alkali, paint).
- 2. This product is suitable for dry surface treatment, avoid water flush and immersion, and ensure its insulation.
- 3. Avoid acid alkaline solution flushing, avoid scratch of transparent protective paint, ensure corrosion resistance.
- 4. The product can't be installed outdoor or where exposed to sunlight.