

No.152 Xingguang Road, Xingguang industry zone, Liushi town, Yueqing, Wenzhou, China ,325604

Wenzhou Safewire Electric CO.,Ltd.

SPECIFICATION SHEET

PRODUCT NAME: 15A switch socket





KC1-014

KC1-040

ADD: 152 xinguang industrial zone, yueqing city, zhejiang province

(TEL) :0086-18612380398

(E-mail): info@safewirele.com (WEB): http://www.safewirele.com

Product Details

Serial No.	Parameter	Description
1	Place of Origin	Zhejiang, China
2	Brand Name	Safewire or OEM Brand
3	Panel Material	PC
4	Back	PC or PC+IRON
5	Inside	phosphor cooper
6	Touch point	silver alloy
7	Rated Current	15A
8	Rated voltage	220~250V
9	Mechanical Life	40000times
10	Color	White
11	Certificate	CE/IEC/SASO/COC
12	Style	Wall Socket
13	Warranty	10 years

Product Show:



15A switched socket with neon

KC1-014

15A/250V~ 10pcs/box 100pcs/ctn 49.5x31.5x20cm³



Double 15A switched socket with neon

KC1-040

15A/250V~ 6pcs/box 60pcs/ctn 49.5x31.5x20cm³

Wenzhou Safewire Electric Co.,Ltd.

No.152 Xingguang Road, Xingguang industry zone, Liushi town, Yueqing, Wenzhou, China ,325604

Features:

- 1.86*86 size, the most popular size in the market.
- 2.High-quality PC material.Flame retardant,high strength,high temperature resistance,not easy to fade.
- 3. Silver contacts, conductive, arc resistant, Tin phosphorus bronze current carrying gold parts, excellent electrical conductivity.
- 4. Precise structure, switch facepllate all in one, easy to assemble and dismantle.

Products inside: Brass and Copper, Silvery touching point









Application:

Residential / General-Purpose, House, Indoor, School, Office, Building, Hotel, Residential, villa, home.



Wenzhou Safewire Electric Co.,Ltd.

No.152 Xingguang Road, Xingguang industry zone, Liushi town, Yueqing, Wenzhou, China ,325604

Attentions:

- 1. When installing and wiring, Product should avoid direct contact with corrosive liquid, gas (strong acid, strong alkali, paint).
- 2. This product is suitable for dry surface treatment, avoid water flush and immersion, and ensure its insulation.
- 3. Avoid acid alkaline solution flushing, avoid scratch of transparent protective paint, ensure corrosion resistance.