

Wenzhou Safewire Electric Co.,Ltd.

2nd floor, Wealth Garden, Liushi Town, Yueqing city,Wenzhou,Zhejiang,China Tel:0086-577-61725369; Email:info@safewirele.com;

www.safewirele.com

SPECIFICATION SHEET

PRODUCT NAME: RCA sockets

PRODUCT No.: M-8081099



ADD: 152 xinguang industrial zone, yueqing city, zhejiang province

(TEL):0086-577-62799688
(E-mail): info@safewirele.com
(WEB): http://www.safewirele.c



Wenzhou Safewire Electric Co.,Ltd.

2nd floor, Wealth Garden, Liushi Town, Yueqing city,Wenzhou,Zhejiang,China Tel:0086-577-61725369; Email:info@safewirele.com;

www.safewirele.com

Product Description

1 Todate Description	
Item No.	M-8081099
Size	22.5*45MM
Port Type	Dual ports
Brand	Safewire
Type of connectors	Video Socket & Audio Socket
Impedance	50Ω,75Ω
Insulation Resistance	≥5000ΜΩ
Durability	500 times
Materials	brass+ABS
Storage	-30°C to +70°C
DC Loop Resistance	52 ohms per 1,000 ft
Center Contact	≤ 1.5 ohm
Frequency range	0~2GHz
External resistance	≤0.2mΩ
Center Pin	Gold-plated pure Copper
Frequency response	DC to 8 MHz
Humidity	0 to 95%
Withstand Voltage	1500V rms

Product Show:







Wenzhou Safewire Electric Co.,Ltd.

2nd floor, Wealth Garden, Liushi Town, Yueqing city,Wenzhou,Zhejiang,China Tel:0086-577-61725369; Email:info@safewirele.com;

www.safewirele.com

Feature

- 1).2 female RCA connectors for stereo audio and composite video
- 2). This RCA audio connector color is Red or yellow.
- 3). Screw to RCA
- 4). This RCA audio connector is pure copper.
- 5)This RCA audio connector gold plating and anti-oxidation, so it is not easy to become black.
- 6). This RCA audio connector applies to audio cable or Audio Equipment etc.
- 7). Useful in covering Female F equipment Jacks to an RCA female connection
- 8). High retention center conductor seizing mechanism
- 9). Precision machined threads provide smooth connection thread mating
- 10).Low insertion loss provides excellent performance
- 11). Return los performance ideal for video and audio frequencies

Application:

Module of 45 x 22.5 mm compatible with the modular plate system of 80 x 80 mm. It has 2 female RCA connectors for stereo audio and composite video. Module based on 2 female RCA connectors on the front. These connectors are for composite video (1 x RCA female yellow) and for stereo audio (1 x RCA female red). On the inside it has connection terminals to the audio and video cables (4 terminalis).

RoHS Certificate of Compliance: Conforms with the Directive 2002/95/EC (ROHS)