



Wenzhou Safewire Electric Co.,Ltd.

2nd floor, Wealth Garden, Liushi Town, Yueqing city,Wenzhou,Zhejiang,China
Tel:0086-577-61725369; Email:info@safewirele.com;

www.safewirele.com

Wenzhou Safewire Electric CO.,Ltd.

SPECIFICATION SHEET

PRODUCT NAME: Keystone Jack Module

PRODUCT No. : M-NE-88B



ADD: 152 xinguang industrial zone, yueqing city, zhejiang province

(TEL) :0086-577-62799688

(E-mail) : info@safewirele.com

(WEB): <http://www.safewirele.com>



Wenzhou Safewire Electric Co.,Ltd.

2nd floor, Wealth Garden, Liushi Town, Yueqing city,Wenzhou,Zhejiang,China
Tel:0086-577-61725369; Email:info@safewirele.com;

www.safewirele.com

Product Description

Item No.	M-NE-88B
Category	CAT5E,CAT6
TIA/EIA	568A/B coded
Terminal	Krone IDC
Type	Unshielded
Size	25*50mm
Brand	Safewire
Material	Panel: ABS; Inside part: Copper;Touch point : Silver alloy touch point
Color	White/Black optional
Mechanical Life	50,000 Times

Product Show:



Product description

Safewire Feed-Thru RJ45 keystone jack modules is including CAT5e,CAT6 Keystone of 8-position 8-conductor (8P8C) & shutter and designed for computer networking. 568A and 568B color wiring diagram is integrated on the lid for easy installation. The modular plugs are manufactured from high-impact clear poly-carbonate to withstand everyday wear and tear.



Wenzhou Safewire Electric Co.,Ltd.

2nd floor, Wealth Garden, Liushi Town, Yueqing city, Wenzhou, Zhejiang, China
Tel:0086-577-61725369; Email:info@safewirele.com;

www.safewirele.com

*Applicable for: Compatible with field-configurable panels and 86*86mm/86*146mm work area faceplate ; Slim profile design for the high density applications.

* CAT6 rated connector provide excellent performance for data networks 100MHZ/120Mbps speed and bandwidth.

* PCB technology provides maximum performance and superior signal quality.

* Gold plated contacts and easy snap-in retaining clip ensure a secure and corrosion free connection.

* Using high quality poly-arbonate flame retardant materials as UL94V-0.

* Includes an integrated TIA-568A/B color wiring diagram.

* Backwards compatible to all lower rated category components.

* The modules are particular used for where space is limited such as in floor box.

* Applicable wire gauge: 22 to 26AWG.

* Rear IDC (Insulation Displacement Connector) type contacts offer effortless of termination and improved wire retention:.

Technical Spec.:

1. Electrical:

1.1. Insulation Resistance: Min 500 MOhm @100 Vdc.

1.2. Dielectric Withstanding voltage/Compressive strength: 1,000 Vdc/ac peak contact-to-contact @ 60 Hz for 1 min.

1.3. Spring Wire Contact Resistance: Max. 20 mOhm.

1.4. IDC Contact Resistance: Max. 2.5 mOhm.

2. Mechanical:

2.1. Dimensions: D: 34.42mm/1.35"; W: 23.03mm/0.91"; H: 45mm/1.77";

2.2. Wiring diagram: TIA/EIA568 OR ISO/IEC11801 standard; IDC wiring: 180 degree IDC twisted Pairs;

2.3. Total Contact Force: Min 800 g for 8 wire leads.

2.4. Retention: 50 N(11 lbf) for 60+_5 S;

2.5. Mating Cycle Life: Min 750 cycles;

3. Construction:

3.1. Housing: Fire retardant PC material: UL94V-0;

3.2. Jack Spring Wire: Phosphor Bronze alloy plated with 50 Uin of gold over 70 to 100 Uin of nickel;

3.3. IDC: IDC110 type, phosphor Bronze alloy with 100 Uin 100% tin alloy; 22-26AWG conductor;

Installation Instructions:

1. **Insert Prepared Jack:** Strip off cable jacket to expose approximately 3/4" /1.90mm of wires .



Wenzhou Safewire Electric Co.,Ltd.

2nd floor, Wealth Garden, Liushi Town, Yueqing city,Wenzhou,Zhejiang,China
Tel:0086-577-61725369; Email:info@safewirele.com;

www.safewirele.com

Then wire jack to preferred wiring scheme.

2. **Punch& Cut:** Insert jack into your termination tool and press firmly down to terminate and cut excess wire.
3. **Installation:** Slide terminated jack out of the Termination Tool. And install supplied IDC cap onto jack.
4. **Snap into:** Ready to snap into the faceplate or panel.

RoHS Certificate of Compliance: Conforms with the Directive 2002/95/EC (ROHS)